THERMAL PRINTER TEST


80 mm receipt · 72 mm = 576 dots · 203 dpi




Edge ruler (mm). Both side lines and the last tick must print; if not, the driver paper width is wrong.

Solid black: white vertical lines = dead or dirty heating dots; lighter on one side = uneven head pressure.

Density ladder (ordered dither)





1-dot / 2-dot combs and lines: fuzzy or merged = darkness too high or speed too fast.

Text:

The quick brown fox 0123456789

The quick brown fox 0123456789

The quick brown fox 0123456789

The quick brown fox 0123

Vietnamese: Đã in đúng dấu: ă â đ ê ô ơ ư Ă Â Đ Ê Ô Ơ Ư ắ ằ ẳ ẵ ặ ấ ầ ẩ ẫ ậ ế ề ể ễ ệ ố ồ ổ ỗ ộ ớ ờ ở ỡ ợ ứ ừ ử ữ ự ý ỳ ỷ ỹ ỵ

Symbols: € £ ¥ ₫ © ° ± × ÷ ½

Barcodes: scan each with a phone.



Code 128: TEST-0123



QR opens this test online



EAN-13: 5901234123457

example-file.com/en/thermal-printer-test-page/

Date _____ Printer _____

example-file.com

✂ cut here